



## Carrier and conveyor roller TRK for medium loads – Steel tubing Ø 50, 60, 80

- **Axle:** Steel, bright-drawn, axle ends with external thread, internal thread, spring axle or spanner flat.
- **Bearing:** Model TRK 50, 60, 80 manufactured from deep drawn sheet steel with grooved ball bearing 6003 or 6202, optionally available with ZZ or RS.
- Please specify the exact model when ordering: roller Ø, axle Ø, axle type, roller length (RL), fitting length (EL) and axle length (AL).
- **Use:** for driven and non-driven roller conveyors. Higher load, speed and running smoothness than TRG.
- **Options:** with splash-water protection for A12 + A15

- for high speed A15; A17 (all steel construction)
- **Order example:**  
TRK/50x1.5/ST/A10/M10 EL= 300 mm or  
TRK/80x2/ST/A17/SW14 EL= 950 mm

Other models are available on request

Order No.	Precision tubing	Axle Ø	mm			mm		mm		mm		
	D x W	A	M	G	F	IG	F	G	F	SW	G	F
TRK/40 x 1.5/ST/A12	40 x 1.5	12	M12	15	12	M8	5	10		10	10	5
TRK/50 x 1.5/ST/A8	50 x 1.5	8	M8	15	11.5	-	-	10	5	-	-	-
TRK/50 x 1.5/ST/A10	50 x 1.5	10	M10	15	11	M6	5	10	5	8	10	5
TRK/50 x 1.5/ST/A12	50 x 1.5	12	M12	15	12	M8	5	10	5	10	10	5
TRK/50 x 1.5/ST/A14	50 x 1.5	14	M14	20	13	M10	5	10	5	12	10	5
TRK/50 x 1.5/ST/A15	50 x 1.5	15	M14	20	13	M10	5	10	5	12	10	5
TRK/50 x 1.5/ST/A17	50 x 1.5	17	M16	20	13	M12	5	-	-	14	10	5
TRK/50 x 2/ST/A8	50 x 2.0	8	M8	15	11.5	-	-	10	5	-	-	-
TRK/50 x 2/ST/A10	50 x 2.0	10	M10	15	11	M6	5	10	5	8	10	5
TRK/50 x 2/ST/A12	50 x 2.0	12	M12	15	12	M8	5	10	5	10	10	5
TRK/50 x 2/ST/A14	50 x 2.0	14	M14	20	13	M10	5	10	5	12	10	5
TRK/50 x 2/ST/A15	50 x 2.0	15	M14	20	13	M10	5	10	5	12	10	5
TRK/50 x 2/ST/A17	50 x 2.0	17	M16	20	13	M12	5	-	-	14	10	5
TRK/60 x 2/ST/A10	60 x 2.0	10	M10	15	11	M6	5	10	5	8	10	5
TRK/60 x 2/ST/A12	60 x 2.0	12	M12	15	12	M8	5	10	5	10	10	5
TRK/60 x 2/ST/A14	60 x 2.0	14	M14	20	13	M10	5	10	5	12	10	5
TRK/60 x 2/ST/A15	60 x 2.0	15	M14	20	13	M10	5	10	5	12	10	5
TRK/60 x 2/ST/A17	60 x 2.0	17	M16	20	13	M12	5	-	-	14	10	5
TRK/80 x 2/ST/A12	80 x 2.0	12	M12	15	12	M8	5	10	5	10	10	5
TRK/80 x 2/ST/A14	80 x 2.0	14	M14	20	13	M10	5	10	5	12	10	5
TRK/80 x 2/ST/A15	80 x 2.0	15	M14	20	13	M10	5	10	5	12	10	5
TRK/80 x 2/ST/A17	80 x 2.0	17	M16	20	13	M12	5	-	-	14	10	5