



## Vulkollan heavy-duty drive wheels

450 - 1700 kg

Wheels

### Wheel series VVA:

- ▶ Special grey cast iron wheel centre
- ▶ With close tolerance bore and groove according to DIN 6885 as driving wheel
- ▶ Moulded Vulkollan running surface, approx. 92° Shore hardness A



Order No.	mm	mm	mm	mm	mm	kg
VVA/100/50/G	100	50	25	50	-	450
VVA/125/50/G	125	50	35	50	60	560
VVA/150/50/G	150	50	35	50	60	660
VVA/160/50/G	160	50	35	50	60	720
VVA/180/55/G	180	55	35	60	60	800
VVA/200/50/G	200	50	35	60	65	1000
VVA/200/80/G	200	80	50	80	75	1200
VVA/250/50/G	250	50	50	60	90	1100
VVA/250/80/G	250	80	50	80	101	1700
VVA/300/60/G	300	60	50	65	82	1600

## Polyurethane wheels

250 - 2100 kg

Wheels

### Wheel series 4:

- ▶ Special grey cast iron wheel centre with plain bearing
- ▶ Moulded polyurethane running surface, approx. 95° Shore hardness A
- ▶ Strong hub with core hole



Order No.	mm	mm	mm	mm	mm	kg
4/100/30/2G	100	30	15	36	48	250
4/125/35/2G	125	35	15	47	48	330
4/150/40/4G	150	40	20	47	61	500
4/200/50/4G	200	50	20	52	66	1000
4/250/60/5G	250	60	25	65	73	1400
4/300/70/5G	300	70	25	70	91	2100

- ▶ Available with groove on request