

Wheel series PO







80 - 2000 kg

Wheels with plain bearing

Wheel series PO:







- ▶ Manufactured from polyamide 6 with **plain-, roller- and ball bearing**
- ▶ Temperature resistance: -40°C to +90°C
- ▶ High chemical resistance
- ▶ Polyamide 6 can absorb and release moisture



Order No.	 mm	 mm	 mm	 mm	 mm	 kg
PO/040/33/35/0G	40	33	10	35	16	80
PO/050/19/22/0G	50	19	10	22	16	50
PO/050/25/28/0G	50	25	10	28	18	150
PO/075/24/28/1G	75	24	12	28	24	150
PO/080/33/35/4G	80	33	20	35	voll	500
PO/100/40/48/2G	100	40	15	48	50	500
PO/125/43/58/4G	125	43	20	58	37	450
PO/125/50/60/4G	125	50	20	60	55	800
PO/150/40/50/2G	150	40	15	50	36	400
PO/150/40/53/4G	150	40	20	53	65	700
PO/160/40/58/4G	160	40	20	58	36	400
PO/160/50/58/4G	160	50	20	58	70	850
PO/200/40/50/2G	200	40	15	50	44	450
PO/300/60/70/6G	300	60	30	70	140	2000







500 - 1000 kg

Wheels with roller bearing

Order No.	 mm	 mm	 mm	 mm	 mm	 kg
PO/080/33/35/2R	80	33	15	35	voll	500
PO/100/40/48/2R	100	40	15	48	50	600
PO/125/38/48/2R	125	38	15	48	70	700
PO/200/50/58/4R	200	50	20	58	70	1000

600 - 2000 kg

Wheels with ball bearing

Order No.	 mm	 mm	 mm	 mm	 mm	 kg
PO/100/50/60/4K	100	50	20	60	60	600
PO/125/38/48/4K	125	38	20	48	70	700
PO/125/40/53/4K	125	40	20	53	60	600
PO/150/40/53/4K	150	40	20	53	65	700
PO/150/50/58/5K	150	50	25	58	70	900
PO/250/60/65/5K	250	60	25	65	70	1500
PO/300/60/75/5K	300	60	25	75	92	2000