




Polyamide heavy-duty rollers

Wheel series POKS:


- ▶ Polyamide 6 wheel centre **with plain bearing**
- ▶ High chemical resistance, low rolling resistance
- ▶ High load-bearing capacity, easy running on smooth surfaces

Temperature resistance:
-40°C to +90°C



Housing series LU:

- ▶ Heavy pressed steel plate housing, zinc plated
- ▶ Fork head with double ball bearing
- ▶ Particularly resistant to shock and impact



Housing series LM:

- ▶ Fork head with double ball bearing and **hardened bearing shells**

200 - 1300 kg

Wheels

Order No.	mm	mm	mm	mm	mm	kg
POKS/080/35/1G	80	35	12	40	36	200
POKS/100/35/1G	100	35	12	40	38	300
POKS/125/40/2G	125	40	15	50	50	400
POKS/150/45/4G	150	45	20	60	70	700
POKS/200/50/4G	200	50	20	60	70	1000
POKS/250/60/5G	250	60	25	75	85	1300

200 - 1250 kg

Swivel castors

Order No.	mm	mm	mm	mm	mm	mm	mm	kg
LU/POKS/080/G	80	35	108	40	105x80	80x60	8.5	200
LU/POKS/100/G	100	35	128	40	105x80	80x60	8.5	300
LU/POKS/125/G	125	40	155	40	105x80	80x60	8.5	400
LM/POKS/150/G	150	45	200	45	135x110	105x80	12.5	700
LM/POKS/200/G	200	50	245	57	135x110	105x80	12.5	1000
LM/POKS/250/G	250	60	300	60	135x110	105x80	12.5	1250

200 - 1250 kg

Swivel castors with double

Order No.	mm	mm	mm	mm	mm	mm	mm	kg
LU/POKS/080/GDS-N	80	35	108	40	105x80	80x60	8.5	200
LU/POKS/100/GDS-N	100	35	128	40	105x80	80x60	8.5	300
LU/POKS/125/GDS-N	125	40	155	40	105x80	80x60	8.5	400
LM/POKS/150/GDS-V	150	45	200	45	135x110	105x80	12.5	700
LM/POKS/200/GDS-V	200	50	245	57	135x110	105x80	12.5	1000
LM/POKS/250/GDS-V	250	60	300	60	135x110	105x80	12.5	1250

200 - 1250 kg

Fixed castors

Order No.	mm	mm	mm	mm	mm	mm	mm	kg
BU/POKS/080/G	80	35	108	-	102x90	80x60	8.5	200
BU/POKS/100/G	100	35	128	-	102x90	80x60	8.5	300
BU/POKS/125/G	125	40	155	-	102x90	80x60	8.5	400
BM/POKS/150/G	150	45	200	-	135x110	105x80	12.5	700
BM/POKS/200/G	200	50	245	-	135x110	105x80	12.5	1000
BM/POKS/250/G	250	60	300	-	135x110	105x80	12.5	1250