



Polyamide heavy-duty rollers

200 - 400 kg


Wheels

Wheel series

POKS:

- ▶ Polyamide 6 wheel centre **with ball bearing**
- ▶ Resistant to fracturing even with heavy loads, low rolling resistance
- ▶ Temperature resistance: - 40°C to + 90°C, high chemical resistance

Polyamide 6 can absorb and release moisture



Order No.



mm



mm



mm



mm



mm



kg

| | | | | | | |
|----------------|-----|----|----|----|----|-----|
| POKS/080/35/1K | 80 | 35 | 12 | 40 | 36 | 200 |
| POKS/100/35/1K | 100 | 35 | 12 | 40 | 38 | 300 |
| POKS/125/40/2K | 125 | 40 | 15 | 50 | 50 | 400 |

200 - 400 kg

Swivel castors



Order No.



mm



mm



mm



mm



mm



mm



mm



kg

| | | | | | | | | |
|--------------|-----|----|-----|----|----------|---------|---|-----|
| LPL/PO/080/K | 80 | 35 | 125 | 30 | 105 x 80 | 80 x 60 | 9 | 200 |
| LPL/PO/100/K | 100 | 35 | 135 | 30 | 105 x 80 | 80 x 60 | 9 | 300 |
| LPL/PO/125/K | 125 | 40 | 160 | 32 | 105 x 80 | 80 x 60 | 9 | 400 |

200 - 400 kg

Swivel castors with double brake



Order No.



mm



mm



mm



mm



mm



mm



mm



kg

| | | | | | | | | |
|----------------|-----|----|-----|----|----------|---------|---|-----|
| LPL/PO/080/KDS | 80 | 35 | 125 | 30 | 105 x 80 | 80 x 60 | 9 | 200 |
| LPL/PO/100/KDS | 100 | 35 | 135 | 30 | 105 x 80 | 80 x 60 | 9 | 300 |
| LPL/PO/125/KDS | 125 | 40 | 160 | 32 | 105 x 80 | 80 x 60 | 9 | 400 |

200 - 400 kg

Fixed castors



Order No.



mm



mm



mm



mm



mm



mm



mm



kg

| | | | | | | | | |
|--------------|-----|----|-----|---|----------|---------|---|-----|
| BPL/PO/080/K | 80 | 35 | 125 | - | 105 x 80 | 80 x 60 | 9 | 200 |
| BPL/PO/100/K | 100 | 35 | 135 | - | 105 x 80 | 80 x 60 | 9 | 300 |
| BPL/PO/125/K | 125 | 40 | 160 | - | 105 x 80 | 80 x 60 | 9 | 400 |

Housing series

LPL:

- ▶ Heavy welded steel construction, zinc plated
- ▶ Fork head with **hardened bearing shells and tapered roller bearing**, lubrication nipple
- ▶ Centre bolt screwed and secured



Castors with directional locking devices are available on request