



Elastic-solid rubber castors

120 - 650 kg

Wheels

Räder – Serie F3:

- ▶ Die-cast aluminium wheel centre with **ball bearing**
- Elastic-solid rubber running surface, approx. 65° Shore hardness A


High elasticity with low rolling resistance



Order No.	mm	mm	mm	mm	kg
F3/080/35/1K	80	35	12	40	120
F3/100/40/1K	100	40	12	40	180
F3/125/40/4K	125	40	20	50	200
F3/160/50/4K	160	50	20	60	300
F3/200/50/4K	200	50	20	60	400
F3/200/50/5K	200	50	25	60	400
F3/250/50/5K	250	50	25	50	500
F3/300/60/6K	300	60	30	60	650

120 - 400 kg

Swivel castors



Housing series LCW:

- ▶ Standard steel plate housing, galvanised
- ▶ Fork head with **double ball bearing**
- ▶ Sealing with integrated ball spacers



Order No.	mm	mm	mm	mm	mm	mm	mm	kg
LCW/F3/080/K	80	35	103	36	105 x 80	80 x 60	9	120
LCW/F3/100/K	100	40	125	36	105 x 80	80 x 60	9	180
LCW/F3/125/K	125	40	155	36	105 x 80	80 x 60	9	200
LCW/F3/160/K	160	50	193	52	135 x 110	105 x 80	11	300
LCW/F3/200/K	200	50	235	54	135 x 110	105 x 80	11	400
LCW/F3/250L/K	250	50	290	66	135 x 110	105 x 80	11	400

120 - 400 kg

Swivel castors with double



Order No.	mm	mm	mm	mm	mm	mm	mm	kg
LCW/F3/080/KDS-N	80	35	103	36	105 x 80	80 x 60	9	120
LCW/F3/100/KDS-N	100	40	125	36	105 x 80	80 x 60	9	180
LCW/F3/125/KDS-N	125	40	155	36	105 x 80	80 x 60	9	200
LCW/F3/160/KDS-N	160	50	193	52	135 x 110	105 x 80	11	300
LCW/F3/200/KDS-N	200	50	235	54	135 x 110	105 x 80	11	400
LCW/F3/250L/KDS-N	250	50	290	66	135 x 110	105 x 80	11	400

120 - 400 kg

Fixed castors



Order No.	mm	mm	mm	mm	mm	mm	mm	kg
BCW/F3/080/K	80	35	103	-	102 x 85	80 x 60	9	120
BCW/F3/100/K	100	40	125	-	102 x 85	80 x 60	9	180
BCW/F3/125/K	125	40	155	-	102 x 85	80 x 60	9	200
BCW/F3/160/K	160	50	193	-	135 x 114	105 x 80	11	300
BCW/F3/200/K	200	50	235	-	135 x 114	105 x 80	11	400
BCW/F3/250L/K	250	50	290	-	135 x 114	105 x 80	11	400



All swivel castors and swivel castors with double brake up to 200 mm ø can also be supplied with 12 mm bolt hole attachment for the same price!