




Polyurethane lift truck castors

Lift truck castors
400 - 900 kg

Order No.	 mm	 mm	Ball bearing seat mm	 kg
VN80/050KS	80	50	47x14	400
VN80/070KS	80	70	47x14	450
VN82/050KS	82	50	47x14	350
VN82/060KS	82	60	47x14	450
VN82/070KS	82	70	47x14	500
VN82/080KS	82	80	47x14	600
VN82/090KS	82	90	47x14	650
VN82/100KS	82	100	47x14	700
VN85/050KS	85	50	47x14	350
VN85/060KS	85	60	47x14	450
VN85/070KS	85	70	47x14	550
VN85/075KS	85	75	47x14	575
VN85/080KS	85	80	47x14	600
VN85/090KS	85	90	47x14	700
VN85/100KS	85	100	47x14	800
VN85/110KS	85	110	47x14	850
VN85/120KS	85	120	47x14	900



Wheel series VN:

- ▶ Steel wheel centre with **ball bearing seat KS47X14**
- ▶ Moulded polyurethane running surface, 92° - 95° Shore hardness A
- ▶ Elastic, quiet run; low abrasive wear

Instead of the ball bearing seat all castors are also available with ball bearings pressed-in on both sides.







Axle diameter 17mm = article ending 3K suitable ball bearing = ball bearing seat 6003
 Axle diameter 20mm = article ending 4K suitable ball bearing = ball bearing seat 6204
 Axle diameter 25mm = article ending 5K suitable ball bearing = ball bearing seat 6005

Order example:

KN80/060KS with 20 mm bore in ball bearing: KN80/060/4K

Polyurethane wheels

Wheels
700 kg

Order No.	 mm	 mm	 mm	 mm	 kg	
PA/200/50/4K/A	200	50	20	60	700	KULA
PA/200/50/5K/A	200	50	25	60	700	KULA



Wheel series PA:

- ▶ Die-cast aluminium wheel centre **with ball bearing**
- ▶ Moulded polyurethane running surface, 92° +/- 3° Shore hardness A
- ▶ Elastic, quiet run, low abrasive wear
- ▶ With cylindrical running surface